

AMBER 5000, 930 (BBL), WIDE FLOOD, WHITE


ITAB

- ✓ Unauffällig und sauber wirkende Decke
- ✓ Verfügbar in verschiedenen Größen und Lumenpaketen
- ✓ Erhältlich mit speziellem ovalen Reflektor für empfindliche Ausstellungsstücke
- ✓ Erhältlich in Weiß, Schwarz und Grau
- ✓ Versenkbar und drehbar



TECHNICAL SPECIFICATION

| | |
|------------------------------|-----------------------|
| Product Code | 282-535-10 |
| Colour | White |
| Control | On/off |
| CRI light colour | 930 (BBL) |
| Delivered lumen output lm | 4740 |
| Driver | Stand alone, included |
| EEI | A+ |
| Light distribution | Wide flood |
| Lightsource | LED COB |
| Mains input voltage | 220-240 V |
| Measurements A | 170 |
| Measurements B | 115,5 |
| Measurements C | 150 |
| Mounting | Recessed |
| Position | 360°/60° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class III |
| Sawing instructions diameter | 160 |
| Start Time | Instant |
| System power W | 48 |
| Unit | mm |
| Weight | 0,92 |



A= 170mm, B= 115,5mm, C= 150mm

| Spot | 14° | Medium | 26° | Flood | 37° | Wide Flood | 55° |
|------|------|--------|------|-------|------|------------|------|
| m | o | m | o | m | o | m | o |
| 1.0 | 0.24 | 1.0 | 0.47 | 1.0 | 0.68 | 1.0 | 1.05 |
| 2.0 | 0.48 | 2.0 | 0.94 | 2.0 | 1.35 | 2.0 | 2.10 |
| 3.0 | 0.72 | 3.0 | 1.41 | 3.0 | 2.03 | 3.0 | 3.15 |



160mm

ITAB

Phone: +46 910 733 790
info@nordiclight.se

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours