

AMBER MINI 3000, 930 (BBL), WIDE FLOOD, BLACK


ITAB

- ✓ Unauffällig und sauber wirkende Decke
- ✓ Erhältlich in verschiedenen Größen und Lumenpaketen
- ✓ Werkzeuglose Montage
- ✓ Erhältlich in Weiß, Schwarz und Grau
- ✓ Versenkbar und drehbar



TECHNICAL SPECIFICATION

| | |
|------------------------------|-----------------------|
| Product Code | 296-773-20 |
| Colour | Black |
| Control | On/off |
| CRI light colour | 930 (BBL) |
| Delivered lumen output lm | 2700 |
| Driver | Stand alone, included |
| EEl | A++ |
| Light distribution | Wide flood |
| Lightsource | LED COB |
| Mains input voltage | 220-240 V |
| Measurements A | 131 |
| Measurements B | 101 |
| Measurements C | 114 |
| Mounting | Recessed |
| Position | 360°/60° |
| Lifetime | L80 B10, 50.000h |
| Protection | IP 20, class III |
| Sawing instructions diameter | 124 |
| Start Time | Instant |
| System power W | 22 |
| Unit | mm |
| Weight | 0,55 |



A= 131mm
B= 101mm
C= 114mm

| Spot | Medium | | Flood | | Wide Flood | | |
|------|--------|-----|-------|-----|------------|-----|------|
| | 16° | 28° | 40° | 65° | | | |
| m | ø | m | ø | m | ø | m | ø |
| 1.0 | 0.28 | 1.0 | 0.50 | 1.0 | 0.73 | 1.0 | 1.28 |
| 2.0 | 0.56 | 2.0 | 1.00 | 2.0 | 1.46 | 2.0 | 2.56 |
| 3.0 | 0.83 | 3.0 | 1.51 | 3.0 | 2.18 | 3.0 | 3.84 |



124mm

ITAB

Phone: +46 910 733 790
info@nordiclight.se

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours