

LOCKER - PARCEL

ITAB

- ✓ Sovitettavissa mihin tahansa lokerokokoon tilaa säästävän toimitusratkaisun mahdollistamiseksi mille tahansa asiakastilaukselle.
- ✓ Joustava ratkaisu kustannustehokkaaseen kokoonpanoon ja kehittämiseen ajan mittaan.
- ✓ Toimitetaan käyttövalmiina (plug-and-play), mahdollistaen helpon ja nopean asennuksen.
- ✓ Älykkään alustan avulla hallinnoit nopeasti ja tehokkaasti kaikkia Click and Collect -ratkaisujasi yhdellä käyttöliittymällä.
- ✓ Käytä osana brändisi ilmettä joustavilla materiaali- ja väri vaihtoehtoilla.



TECHNICAL SPECIFICATION

Dimensions HxLxW mm	Sections of 1770x1140x673
Weight kg	Up to 392kg per section
Certifications	CE
Voltage	240VAC 50Hz
Operating temperature	0°C to +40°C
Communication	LAN/3G/4G
Options	Material/Slot sizes/Colour
Customisable	Yes
Installation	Indoor
Scanners	Omnidirectional presentation scanner
Slot sizes	Various
Parcel sizes	Various
Operating conditions	40% to 60%, (non- condensing)
Temperature zones	Ambient

ITAB HQ Sweden
Phone: +46 36 31 73 00
info@itab.com

Local contact
Please visit
www.itab.com/contact

Please note that this product sheet is for a specific product and colour. The pictures may show examples of other available colours